



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER	A	B	C	D	E	F	G	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MAX IN (mm)	IN (mm) +/- .125 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)		
AL(P,R)-13-150-DL-IT-30	1.30 (33.02mm)	13.547 (344.093mm)	.054 (1.371mm)	.503 (12.776mm)	.747 (18.973mm)	.741 (18.821mm)	1.107 (28.117mm)	.244 (6.197mm)	150 (670)	HB
AL(P,R)-19-150-DL-IT-30	2.30 (58.42mm)	19.818 (503.377mm)	.057 (1.447mm)	.505 (12.827mm)	.747 (18.923mm)	.741 (18.770mm)	1.122 (28.498mm)	.244 (6.172mm)	150 (670)	HB



150 LB. DUAL LOOP SERIES CABLE TIES WITH 1/4 INCH MOUNTING HOLE

COLOR DESIGNATIONS:

MATERIAL:

IT-30 = IMPACT RESISTANT, UV BLACK HEAT STABILIZED

NYLON 6/6 POLYAMIDE

C	3/7/18	PB	EG	EG	DELETED HIGH TEMP FROM COLOR DESIGNATION	SHEET 1 OF 1	REV.: C	DRAWING NO.: IMPACT-DL-C	
B	1/25/18	PB	VA	VA	UPDATE DIMENSIONS	DRAWN BY	DATE	CHECK	SCALE
A	1/8/2018	PB	VA	VA	INITIAL RELEASE	PB	1/8/18	VA	NONE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION				

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.95.2