



SPECIFICATIONS	KEY FEATURES	3 POLE
NEMA 4, 12 3 Pole 10 ⁶ Mechanical Operations 6 Amp, 400V AC 10mA min. current -22° F + 176° F min/max temp. 11 lbs. Door Holding Force Key Entry Rotates 4 x 90° Cable Entry Thread M20 + 1/2" NPT UL, CSA, CE, BG, IEC 947-5-1 BG Safety Agency Approved	• Eight key entry locations ★ • Screw Terminals • Quick Connect Option • Glass Reinforced Thermoplastic • Positive Opening N.C. contact → • Tamper Resistant • 2" Min. Closing Radius "MRU" key, Die Cast Aluminum • Stainless Steel M-3 key, 6" min. Closing Radius ★ Switch head rotates, permits <u>four different side</u> and <u>four top</u> key entry locations.	Narrow Profile for Confined Spaces  SKI Series \$58 List Price Actuator keys sold separately. See page 6.

601.6869.145

Part #	SKI-UV15Z F150 M3
Contact layout → (with key inserted)  Slow-Action  Contact travel mm (inch) Tol. ± 0.25 mm Actuating force N Tol. ± 10% Switch angle degrees Tol. ± 3.5° Actuating torque Nm Tol. ± 10% In Out () actuator in () actuator out	

Technical Specifications

Contacts:

Sliver - Nickel alloy

Short Circuit Protection:

6A slow blow, 10A fast blow

Max Wire Size:

Standard or Solid
20 AWG (0.5mm²) to
16 AWG (1.5mm²)

Max switching distance per second: 3 ft.

Max switching operations per minute: 30



Quick Connect Option:

See page 25.
For Plug and Socket options.



Metal 1/2" NPT Option:

Non-Metal 1/2" NPT adaptor supplied standard.
For Metal Adaptor, add "ME" to part #.
Example: SKI-UV15Z-ME
(no extra charge)



Cord Grip Cable Gland Option:

Add "GRIP" to part # to replace the standard M20 to 1/2" NPT Adaptor.
For 5mm to 13mm cable diameter
Example: SKI-UV15Z-GRIP
(no extra charge)