



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual Wall-mounting template
Performance multiplier	1
Number of tare power	24 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Workstation
UPS size	WS
Value multiplier	1

Physical

Cable length	1.83 m
Colour	Charcoal
Depth	28.5 cm
Height	8.6 cm
Mounting location	Front
Mounting preference	No preference
Net weight	5.4 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	23 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Input

Network frequency	50/60 Hz
Plug standard	Schuko CEE 7/7P
Input voltage limits	180...266 V
Maximum input current	10 A
Switching current capacity	10 A
Number of cables	1
Input voltage	230 V

## Output

Rated power in W	240 W
Maximum configurable power in W	240 W
Output frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Schuko CEE 7 4 Schuko CEE 7 surge
Curve equation	Efficiency
Curve fixed loss	0.0118
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0.001
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	400 VA
Rated power in VA	400 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE GOST NEMKO
Equipment protection policy	Lifetime : 100000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...50000 ft
Ambient air temperature for storage	0...40 °C

Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Show note OP temperature	No

### Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	A
Battery charger power	6 W rated
Battery power in VAh	102 VAh runtime
Battery life	2...5 year(s)
Extended runtime	0

### Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet

### Packing Units

Package 1 Weight	5.6 kg
Package 1 Height	13.2 cm
Package 1 width	30 cm
Package 1 Length	36.6 cm
SCC14	10731304233364
Number of Units in Package 2	2
Package 2 Weight	12.17 kg
Package 2 Length	381.00 mm
Number of Units in Package 3	48

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---