



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software User manual USB cable
Max runtime	50 min
Performance multiplier	1
Number of tare power	70 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS
Value multiplier	1

Physical

Cable length	2.44 m
Colour	Charcoal
Depth	17.1 cm
Height	10.5 cm
Mounting location	Front
Mounting preference	No preference
Net weight	6.7 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	28.6 cm

Input

Network frequency	45...65 Hz
Plug standard	Australian/Chinese
Input voltage limits	165...266 V
Inputvolt_other	220 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	400 W
Maximum configurable power in W	400 W
Output frequency	47...63 Hz sync to mains
Crest factor	3 : 1
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 chinese outlet
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	95 % (full load)
Graph display	1
Maximum output current	7 A
Output voltage	230 V
Maximum configurable power in VA	650 VA
Rated power in VA	650 VA

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	10...90 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...4572.00 m
Acoustic level	40 dBA
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	24 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	B
Battery charger power	5 W rated

Battery power in VAH	124 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	180 J
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL

Packing Units

Package 1 Weight	7.5 kg
Package 1 Height	11.4 cm
Package 1 width	38.1 cm
Package 1 Length	17.8 cm
SCC14	10731304225666
Number of Units in Package 2	2
Number of Units in Package 3	120

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------