



Commercial status

Discontinued on: 31 December 2013

! To be discontinued

Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

General

Provided equipment	User manual Smart UPS signalling RS-232 cable CD with software
Product web sub-family	Extended run
Performance multiplier	1
Number of tare power	65 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Cable length	2.44 m
Number of rack unit	5U
Colour	Black
Depth	49.5 cm
Height	44.4 cm
Mounting preference	No preference
Net weight	63.64 kg
Mounting mode	Rack-mounted with kit
Two post mountable	0

USB compatible	No
Width	22.1 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA L5-30P
Input voltage limits	75...154 V adjustable 82...144 V
Number of cables	1
Input voltage	120 V

Output

Rated power in W	2700 W
Maximum configurable power in W	2700 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	9 NEMA 5-15R 2 NEMA 5-20R
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	96 % (full load)
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	3000 VA
Rated power in VA	3000 VA
Transfer time	2 ms typical

Conformance

Product certifications	CSA
Standards	FCC part 15 class A UL 1778
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	53 dBA
Heat dissipation	305 Btu/h

Show note OP temperature	No
--------------------------	----

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	B
Battery charger power	271 W rated
Battery power in VAH	816 VAh runtime
Battery life	3...5 year(s)
Battery option	SUA48XLBP 1 2448 VAh SUA48XLBP 2 4080 VAh SUA48XLBP 3 5712 VAh UXABP48 1 4176 VAh UXABP48 2 7536 VAh UXABP48 3 10896 VAh SUA48XLBP 8 13872 VAh SUA48XLBP 10 17136 VAh
Extended runtime	1

Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	82.73 kg
Package 1 Height	55.9 cm
Package 1 width	38.1 cm
Package 1 Length	76.2 cm
Number of Units in Package 3	2

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--