



Commercial status

Discontinued on: 14 January 2021

To be end-of-service on: 31 December 2030

! To be discontinued

Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

General

Provided equipment	CD with software Network management card Power modules ship installed Smart UPS signalling RS-232 cable User manual Installation guide Start up included
Performance multiplier	0
Number of tare power	360 W
Number of power module free slots	0
Number of power module filled slots	1
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	L
Value multiplier	0

Physical

Colour	Black
Depth	107.5 cm
Height	199.5 cm
Mounting location	Front
Mounting preference	No preference
Net weight	656.36 kg
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No
Width	60 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	165...240 V
Inputvolt_other	220 V
Maximum input current	80 A
Switching current capacity	125 A
Input voltage	208 V 3 phases
Cos phi	0.98

Output

Rated power in W	24000 W
Maximum configurable power in W	24000 W
Harmonic distortion	Less than 5 % at full load
Output frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Outputvolt_other	220 V
Crest factor	Unlimited
UPS type	Double conversion online
Wave type	Sine wave
Output connector type	Hard wire 5-wire (3P + N + E) 1
Nb of power socket outlets	5 NEMA L21-20
Bypass type	Built-in maintenance bypass Built-in static bypass
Curve equation	Efficiency
Curve fixed loss	0.0155
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0.0256
Curve square loss	0.0333
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	0
Maximum output current	92 A
Output voltage	120 V 208 V 208 V 3 phases
Maximum configurable power in VA	30000 VA
Rated power in VA	30000 VA

Conformance

Product certifications	CUL listed UL 1778
Standards	ISO 14001 ISO 9001

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-50...40 °C
Storage altitude	0.00...15240.00 m
Acoustic level	58 dBA
Heat dissipation	4238 Btu/h
Show note OP temperature	No
NEMA degree of protection	NEMA 1

Batteries & Runtime

Battery type	VRLA
Number of battery filled slots	3
Number of battery free slots	2
Battery recharge time	3 h
Number of battery replacement quantity	3
Additional information	Configurable for 200 : 208 or 220V 3 Phase nominal output voltage
Liquid value	0
Battery curve	B
Battery charger power	2483 W rated
Battery power in VAh	7474 VAh runtime
Battery life	3...5 year(s)
Battery option	SYBT4 1 9843 VAh SYBT4 2 12235 VAh SUVTBXR6B6S 1 22123 VAh SUVTBXR6B6S 2 36539 VAh SUVTBXR6B6S 3 51329 VAh SUVTBXR6B6S 4 66294 VAh
Extended runtime	0

Communications & Management

Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : configurable delays
Emergency power off	Yes

Packing Units

Package 1 Weight	691.36 kg
Package 1 Height	199.5 cm
Package 1 width	60 cm
Package 1 Length	107.5 cm

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year repair or replace, Start-Up Service
----------	--------------------------------------------