

Zero Smog 6V 100-120 Volt

Product no.: T0053666299N



Benefits

- Mobile fume extraction unit purifies air at up to 8 workplaces (4 typical) The Constant Flow Control (CFC) guarantees optimal air flow regulation for each working place independent of the connected workplaces
- Includes F7 fine dust pre-filter and compact filter with 50% H13 HEPA filter and 50% Chemabsorb Efficiency test via USB port
- Adjustable pressure control optimizes air flow regulation for each work place Electronic filter control with optical and acoustical filter alarm
- Noise dampened metal housing 4 wheels to allow easy movement of the unit
- Remote control via RS 232 port
- Maximum extraction rate 615 m³/h Low noise level



Technical Data

Dimensions L x W x H (mm)	460 x 460 x 665
Dimensions L x W x H (inches)	18,11x18,11x26,18
Weight (approx.) in kg	40
Voltage	120 V, 60 Hz
Power	460 VA
Noise level (distance 1 m) dB(A)	< 51
Max. vacuum	2800 Pa
Capacity m³/h	615
Pre-filter	T0058735836
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon / 50 % Chemisorb)
Max. capacity	1–8 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	The USB port can be used to load firmware updates, run efficiency tests and logdat data.
WX-compatible	on