

P.C.B. LAYOUT



Contact	DIM A	DIM B	Contact	DIM A	DIM B
06	7.62	5.08	18	22.86	20.32
08	10.16	7.62	20	25.40	22.86
10	12.70	10.16	24	30.48	27.94
14	17.78	15.24			
16	20.32	17.78			

Pin:	brass. machined, CuZn38Pb2
Clip:	contact 4 finger: Beryllium copper, heat treated
	plating: HZL = Pin - 200µ" / Clip - gold flash
	HGL = Pin - gold flash / Clip - gold flash
Insualtor body:	polyamide (glass filled) , UL94V-0
Current rating:	3A / contact max.
Contact resistance:	<4mOhm / contact
Insualtions resistance:	>1000Mohm at V=100V
Operating:	60 vac / dc
Operating temperature:	gold plated: -55°C to +125°C
	tin plated: -40°C to +105°C
Soldering temperature:	+260°C, 10s max.
Mechanical life:	min.200

	Datum	Name
Bearb.	07.11.01	Hellwig
Gepr.	07.11.01	Hellwig
Norm.		

IC-sockets
with machined pins
AR xx - HZL-TT
AR xx - HGL-TT

ASSMANN
Electronic Components

Ersatz für ASS 0337 CO
dd. 19.06.2001

Blatt 1/1

Downloaded from Arrow.com.