

e Pi	roduct: <u>38210</u> ⊠		
	L Type PV Wire, #10 Str TC, XI	PO Ins, PVC Jkt, 600V PV 90C	Dry/Wet
	😭 Request Sample		
Product Description UL Type PV Wire, 10AWG (105x	30) Tinned Copper, XLPO Insulation, PVC Outer J	acket, 600V PV 90C Dry/Wet USE-2 RHW-2 SUN R	RES
Technical Specifications			
Product Overview			
Suitable Applications:	Interconnection wiring of grounded and ungrounded photovoltaic p	ower systems as described in Section 690.31(A) of the 2008 NEC.	
Physical Characteristics (Over	all)		
Conductor			
AWG Stranding Material N 10 105x30 TC - Tinned Copper 1	lo. of Conductors		
Conductor Count:	1		
Insulation			
Material Nominal XLP, XLPO, XLPE (Thermoset) 0.048 in XLP, XLPO, XLPE (Thermoset)	Wall Thickness		
Outer Jacket Material			
Material Nominal Diame PVC - Polyvinyl Chloride 0.288 in	ter Nominal Wall Thickness 0.033 in		
Electrical Characteristics			
Conductor DCR Nominal Conductor DCR 0.91 Ohm/1000ft Current			
Element Single conductor in free air @ 30 ambient	Max. Recommended Current [A] 55 amps		
Voltage UL Voltage Rating 600 V			
Temperature Range			
UL Temp Rating:	90°C Wet/Dry		
Operating Temp Range:	-40°C To +90°C		

Mechanical Characteristics

Bulk Cable Weight:	63 lbs/1000ft
Max Recommended Pulling Tension:	136.5 lbs
Min Bend Radius/Minor Axis:	2.875 in

Standards

NEC/(UL) Specification:	PV, RHW-2, USE-2
UL AWM Style:	N/A
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2009-09-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

ltem #	Color	Putup Type	Length	UPC
38210 0101000	Black	Reel	1,000 fl	612825147626
38210 0105000	Black	Reel	5,000 ff	612825147633
Footnote:		C -	CRATE REEL PU	
Product Note	es			
Notes:			Se	parator material o
History				

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.