



Product: <u>5521FE</u> ☑

Security & Sound, 3 Conductor 22 AWG BC, Shielded, Riser

# **Product Description**

Security & Commercial Audio Cable, 3 Conductor 22 AWG solid bare copper conductors with polyolefin insulation, Beldfoil® shield, Riser, PVC jacket with ripcord.

# **Technical Specifications**

#### **Product Overview**

| Suitable Applications:      |                                    |                  |                   | Intercom/PA Systems, Sound/Audio Systems |  |
|-----------------------------|------------------------------------|------------------|-------------------|--|--|
| Physi                       | Physical Characteristics (Overall) |                  |                   |  |  |
|                             |                                    | •                | <u> </u>          |  |  |
| Condu                       | ctor                               |                  |                   |  |  |
| AWG                         | Stranding                          | Material         | No. of Conductors |  |  |
| 22                          | Solid                              | BC - Bare Copper | 3                 |  |  |
| Conductor Count:            |                                    |                  | 3                 |  |  |
| Insulation                  |                                    |                  |                   |  |  |
| IV                          | Material                           | Nominal Wall Th  | ckness            |  |  |
| PP - Polypropylene 0.007 in |                                    |                  |                   |  |  |

# Color Chart

| Number | Color |
|--------|-------|
| 1      | Black |
| 2      | Red   |
| 3      | White |

#### **Outer Shield Material**

| Type | Material       | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|----------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Alum /<br>Poly | Beldfoil®           | 100 %        | TC - Tinned Copper | 22            | Solid                        |

#### **Outer Jacket Material**

| Material                 | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.119 in         | 0.015 in               | Yes     |

### **Construction and Dimensions**

# Cabling



#### **Electrical Characteristics**

#### Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 15.7 Ohm/1000ft       | 11.9 Ohm/1000ft          |

# Capacitance

| Nom. Capacitance Conductor to Cond | luctor Nom. Capacitance Conductor to Other Conductor to Shield |
|------------------------------------|--|
| 31 pF/ft                           | 55.8 pF/ft   |

### Inductance

Nominal Inductance 0.167 µH/ft

### Current

Max. Recommended Current [A]

2.8 Amps per conductor @ 25°C

#### Voltage

UL Voltage Rating
300 V RMS

# **Temperature Range**

| UL Temp Rating:       | 75°C           |
|-----------------------|----------------|
| Operating Temp Range: | -20°C To +75°C |

### **Mechanical Characteristics**

| Bulk Cable Weight:               | 10.8 lbs/1000ft |
|----------------------------------|-----------------|
| Max Recommended Pulling Tension: | 31.2 lbs        |
| Min Bend Radius/Minor Axis:      | 1.25 in         |

# **Standards**

| NEC Articles:            | 800 |
|--------------------------|-----|
| NEC/(UL) Specification:  | CMR |
| CEC/C(UL) Specification: | CMG |

# **Applicable Environmental and Other Programs**

| Environmental Space:                  | Indoor - Riser                |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

# Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT4                   |
|---------------------|-----------------------|
| UL Flammability:    | UL1666 Vertical Shaft |
| UL voltage rating:  | 300 V RMS             |

# Plenum/Non-Plenum

| Plenum (Y/N):  | No     |
|----------------|--------|
| Plenum Number: | 6521FE |

### **Part Number**

# Variants

| Item #          | Color | Putup Type   | Length   | UPC          |
|-----------------|-------|--------------|----------|--------------|
| 5521FE 0081000  | Gray  | Reel         | 1,000 ft | 612825426110 |
| 5521FE 008Z1000 | Gray  | ReelTuff Box | 1,000 ft | 612825164159 |

# History

| Update and Revision: | Revision Number: 0.285 Revision Date: 04-28-2020 |
|----------------------|--|
|                      |  |

#### © 2020 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.