



Product: [9363](#)

High Perform Instr, 1 Tri #22 Str TC, PVC Ins E1, OS, PVC Jkt, PLTC-ER

[Request Sample](#)

Product Description

High Performance Instrumentation, 1 Triad 22AWG (7x30) Tinned Copper, PVC Insulation E1 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

Product Category:	Instrumentation 300V PLTC or PLTC-ER
Suitable Applications:	Instrumentation, Sensors, Valves, Positioners, RTD, 4-20mA, 0-10V

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Triad(s)	1	22	7x30	TC - Tinned Copper

Insulation

Element	Material	Thickness [in]	Color
Triad(s)	PVC - Polyvinyl Chloride	0.017	Black, White, Red

Outer Shield Material

Type	Material	Coverage	Drainwire Type
Tape	Alum / Poly	100%	7x30 - TC

Outer Jacket Material

Material	Nominal Wall Thickness	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	0.037 in	0.210 in	Yes

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Triad(s)	15.0 Ohm/1000ft	26 pF/ft	3.8 Amps per conductor @ 25°C

Mechanical Characteristics

Temperature

UL Rating	Operating
105°C	-30°C to +105°C

Temperature Table Note: AWM 80°C

Bend Radius

Stationary Min.
2 in

Max Recommended Pulling Tension: 33 lbs

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
Sustainability:	CA Prop 65 (CJ for Wire and Cable)=Yes
AWM Compliance:	2464
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS 2

History

Update and Revision:	Revision Number: 0.337 Revision Date: 05-22-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.