



**Product:** [9408](#)

High Perform Instr, 1 Pr #20 Str TC, PVC Ins E2, PVC Jkt, PLTC-ER

[Request Sample](#)

**Product Description**

High Performance Instrumentation, 1 Pair 20AWG (19x32) Tinned Copper, PVC Insulation E2 Color Code, PVC Outer Jacket, PLTC-ER

**Technical Specifications**

**Product Overview**

Suitable Applications:	Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V
------------------------	--

**Construction Details**

**Conductor**

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	20	19x32	TC - Tinned Copper

**Insulation**

Element	Material	Thickness [in]	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.018	Black, Red

**Outer Jacket Material**

Material	Thickness	Diameter	Ripcord
PVC - Polyvinyl Chloride	0.037 in	0.218 in	Yes

**Electrical Characteristics**

**Electricals**

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	9.5 Ohm/1000ft	30 pF/ft	7.6 Amps per conductor @ 25°C

**Voltage**

UL Voltage Rating
300 V (PLTC, CMG), 150 V (ITC)

**Mechanical Characteristics**

**Temperature**

UL Rating	Operating
105°C	-30°C to +105°C

Table Notes:	AWM 80°C
--------------	----------

**Bend Radius**

Stationary Min.
2 in

Max. Pull Tension:	30 lbs
Bulk Cable Weight:	23

**Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, T-29-520, 1202
NEC / UL Compliance:	CMG, ITC-ER, PLTC-ER
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.329 Revision Date: 06-05-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.