



# Product Description

Electronic, 2 Pair 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

# **Technical Specifications**

# **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

# **Physical Characteristics (Overall)**

## Conductor

| Element                | AWG | Stranding | Material           | No. of Pairs |
|------------------------|-----|-----------|--------------------|--------------|
| Pair(s)                | 22  | 7x30      | TC - Tinned Copper | 2            |
| Conductor Count: 4     |     | 4         |                    |              |
| Total Number of Pairs: |     | 2         |                    |              |

#### Insulation

| Element | Material                 | Nominal Wall Thickness |
|---------|--------------------------|------------------------|
| Pair(s) | PVC - Polyvinyl Chloride | 0.011 in               |

## Color Chart

| Number | Color         |  |
|--------|---------------|--|
| 1      | Black & Red   |  |
| 2      | Black & White |  |

#### **Outer Shield Material**

Material No Shield

#### **Outer Jacket Material**

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.233 in         | 0.032 in               |

# **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR 14.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conducto 25.5 pF/ft

# Current

Max. Recommended Current [A] 2.2 Amps per conductor @ 20°C

#### Voltage

| UL Description    | UL Voltage Rating           |  |
|-------------------|-----------------------------|--|
| UL AWM Style 2576 | 150 V RMS UL AWM Style 2576 |  |
| CMG               | 300 V RMS CMG               |  |

#### **Temperature Range**

| UL Temp Rating:       | 80°C (UL AWM Style 2576) |
|-----------------------|--------------------------|
| Operating Temp Range: | -20°C To +80°C           |

# **Mechanical Characteristics**

| Bulk Cable Weight:               | 24 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 36 lbs        |
| Min Bend Radius/Minor Axis:      | 2.5 in        |

#### Standards

| NEC/(UL) Specification:  | CMG                        |
|--------------------------|----------------------------|
| CEC/C(UL) Specification: | CMG                        |
| UL AWM Style:            | UL Style 2576 (150 V 80°C) |
| CPR Euroclass:           | Еса                        |

# **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):        | Yes                           |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

# Flammability, LS0H, Toxicity Testing

| UL Flammability:      | UL1685 FT4 Loading            |
|-----------------------|-------------------------------|
| CSA Flammability:     | FT4                           |
| ISO/IEC Flammability: | IEC 60332-1-2                 |
| UL voltage rating:    | 150 V RMS (UL AWM Style 2576) |

## Plenum/Non-Plenum

Plenum (Y/N):

# **Part Number**

| Variants        |        |              |  |  |
|-----------------|--------|--------------|--|--|
| ltem #          | Color  | UPC          |  |  |
| 9744 0601000    | Chrome | 612825258063 |  |  |
| 9744 060500     | Chrome | 612825258070 |  |  |
| 9744 0601 11000 | Chrome | 6128252580/0 |  |  |

# 9744 0600500 Chrome 612825258070 9744 060U1000 Chrome 612825258070 9744 060U500 Chrome 612825258070 9744 060U500 Chrome 612825258050 Footnote: C - CRATE REEL PUT-UP.

## **History**

Update and Revision:

Revision Number: 0.292 Revision Date: 05-11-2020

#### © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

No

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and

regulations based on their individual usage of the product.