



REV.	DESCRIPTION	DATE	APPROVED
B	Engineering Release	03/15/12	T. Y.
C	Added Note 5	12/10/12	T. Y.



*Length "X.XXX"	Tolerance
1.000" ~ 16.000"	±0.050"
16.250" ~ 40.000"	±0.150"
40.250" ~ 80.000"	±0.300"
80.250" ~ 500.0"	±0.5%

EXAMPLE:
PM5-A2031-6.500
 Series Fiber Length in 0.250" Increments



NOTES:

1. SEALED TO IP67 RATING
2. ROHS COMPLIANT
3. MOUNTING HARDWARE SHIPPED NON-ASSEMBLED
4. INSERT VITON RING ON PANEL MOUNT PRIOR TO PANEL INSERTION
5. ALLOWABLE CUT LENGTH IS UP TO 3 DECIMAL PLACES

STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		 BIVAR [®] 4 THOMAS, IRVINE, CA. 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
DECIMALS	ANGULAR		
.X ± .1	X° ± 1°	 TITLE: IP67 RATED METAL PANEL MOUNT FLP INDICATORS	
.XX ± .02			
.XXX ± .010		PART NO: PM5-A2031-XX.XX REVISION: C	
DESIGNED: Ty Yin	DATE: 03/15/12	CAGE CODE : 32559 SHEET # 1 OF 1	
CHECKED: B. Ollver	DATE: 03/15/12	CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.	