# ACPM-7788



# Multiband Multimode PA Quad-Band GSM/EDGE and MultiMode B1/B2/B3/B4/B34,B39/B5(B26)/B8/B17/B 20/B28A/B28B(B13)

**Product Brief** 

### Description

The ACPM- 7788 is a multiband multimode PA which supports GMSK and 8-PSK modulation schemes and UMTS bands 1, 2, 3, 4, 34, 39, 5, 8, 13, 17, 20, 28A and 28B.

Input and output terminals are internally matched to 50 ohms. The power amplifier is manufactured on an advanced InGaP HBT technology offering state-of-the-art reliability, temperature stability and ruggedness. This module is housed in a cost effective, extremely small and thin 5mmx7mm package.

## **Ordering Information**

Part Number	Number of Devices	Container
ACPM-7788-TR1	1000	178 mm (7 in.) tape/reel

#### Features

- Quad Band GSM/EDGE
- UMTS/LTE: 5 High Band Outputs and 6 Low Band Outputs
- UMTS B1, B2, B3, B4, B34/39, B5(B26), B8, B17, B20, B28A and B28B (B13)
- Small Size (7x5mm2)
- APT Compatible
- High Efficiency with APT
- Compatible with MIPI RFFE
- 42-pin surface mounting package
- Internal 50 Ω matching networks for both RF input and output
- Green- Lead-free and RoHS compliant

#### **Applications**

- GSM850/900, DCS1800/PCS1900
- UMTS/LTE B1, C2K BC6
- UMTS/LTE B2, LTE B25, C2K BC1
- UMTS/LTE B3
- UMTS/LTE B4
- TD-SCDMA B34, B39, TD-LTE B39
- UMTS/LTE B5, LTE B26, C2K BC0 (BC10)
- UMTS/LTE B8
- LTE B17, B20, B28A and B28B (B13)

# Package Dimensions



All dimensions in millimeters

## **Marking Specification**







For product information and a complete list of distributors, please go to our web site: www.avagotech.com

Avago Technologies and the A logo are trademarks of Avago Technologies in the United States and other countries. All other brand and product names may be trademarks of their respective companies.

Data subject to change. Copyright © 2015 Avago Technologies. All Rights Reserved.

pub-005231 - 2015-07-10



