


15320.2
PRS 2 G
PRS 2 G



Relay socket base PRS, for miniature power relay with 2 CO contacts, Screw connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Business data

Product description	Relay socket base with screw connection
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	41.1
Weight per piece (including packaging)	45
Unit of weight	G
Customs number	85366990
Country of origin	CN

15320.2 PRS 2 G PRS 2 G

Technical Data

Dimensions

Length	76 mm
Width	15.7 mm
Height TS 35 / 7.5 with BA	65 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	1.5 mm ²
Stripping length	8 mm
Torque	0.8 Nm

Output data

Switching voltage / switching voltage max.	230 / 400 VAC
Continuous current max. / Inrush current max.	10 A
Contact configuration	2 CO contacts

Materials

Flammability class UL 94	V-0
Working temperature, min.	-25 °C
Working temperature, max.	80 °C

Further technical data © CONTA-CLIP Verbindungstechnik GmbH | Otto-Hahn-Str. 7 | D-33161 Hövelhof
Tel +49 (0) 52 57.98 33-0 | Fax +49 (0) 52 57.98 33-33 | E-Mail info@conta-clip.de | conta-clip.de

Protection	IP20
Insulation voltage coil/contact	4 kV

Creation date 08.06.2020 10:46:31
Subject to technical modifications

Insulation voltage contact/contact

1 kV

15320.2

Pinning

5 mm

PRS 2 G**PRS 2 G****Technical Data**

Datasheet



15320.2
PRS 2 G
PRS 2 G

Approvals

Standards and regulations

CE compliant	✓
--------------	---

15320.2
PRS 2 G
PRS 2 G

Media

