

2205.0
H 1,5/24 RD
H 1,5/24 RD



Wire-end ferrules, Max. wire cross-section: 1.5 mm², Length: 24 mm, Length of copper pipe: 18 mm, Colour: Red

Business data

Product description	Ferrules
Packaging unit	500
Quantity unit	PC
Weight per piece (not including packaging)	0.2
Weight per piece (including packaging)	0.21
Unit of weight	G
Customs number	85369010
Country of origin	DE

2205.0

H 1,5/24 RD

H 1,5/24 RD

Technical Data

Dimensions

Length	24 mm
Length of copper pipe	18 mm
Diameter of copper pipe	1.7 mm
Diameter plastic collar	3.5 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.25 mm

Connection data

Wire cross-section, max.	1.5 mm ²
Wire cross-section AWG, max.	16
Stripping length	20 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

2205.0
H 1,5/24 RD
H 1,5/24 RD

Approvals

Standards and regulations

DIN 46228-4:1990	✓
------------------	---
