

2396.0

H 35,0/18

H 35,0/18



Wire-end ferrules, Max. wire cross-section: 35 mm<sup>2</sup>, Length: 18 mm, Colour: natural

**Business data**

|                                            |          |
|--------------------------------------------|----------|
| Product description                        | Ferrules |
| Packaging unit                             | 500      |
| Quantity unit                              | PC       |
| Weight per piece (not including packaging) | 0.99     |
| Weight per piece (including packaging)     | 1        |
| Unit of weight                             | G        |
| Customs number                             | 85369010 |
| Country of origin                          | DE       |

**2396.0**

**H 35,0/18**

**H 35,0/18**

## Technical Data

---

### Dimensions

---

|                               |        |
|-------------------------------|--------|
| Length                        | 18 mm  |
| Diameter of copper pipe       | 8.3 mm |
| Diameter of feed-in funnel    | 11 mm  |
| Wall thickness of copper pipe | 0.2 mm |

### Connection data

---

|                              |                    |
|------------------------------|--------------------|
| Wire cross-section, max.     | 35 mm <sup>2</sup> |
| Wire cross-section AWG, max. | 2                  |
| Stripping length             | 18 mm              |

### Materials

---

|                           |                                |
|---------------------------|--------------------------------|
| Copper pipe               | Copper alloy                   |
| Surface                   | Galvanically tin-plated, shiny |
| Working temperature, max. | 120 °C                         |

2396.0

H 35,0/18

H 35,0/18

## Approvals

---

## Standards and regulations

---

|                  |   |
|------------------|---|
| DIN 46228-1:1992 | ✓ |
|------------------|---|

---