

2621.0

H 0,25/12 LB

H 0,25/12 LB



Wire-end ferrules, Max. wire cross-section: 0.75 mm², Length: 14 mm, Length of copper pipe: 8 mm, Colour: Light-blue

Business data

Product description	Ferrules
Packaging unit	500
Quantity unit	PC
Weight per piece (not including packaging)	0.06
Weight per piece (including packaging)	0.07
Unit of weight	G
Customs number	85369010
Country of origin	DE

2621.0

H 0,25/12 LB

H 0,25/12 LB

Technical Data

Dimensions

Length	14 mm
Length of copper pipe	8 mm
Diameter of copper pipe	1.2 mm
Diameter plastic collar	3.4 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.25 mm

Connection data

Wire cross-section, max.	0.75 mm ²
Wire cross-section AWG, max.	18
Stripping length	10 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

2621.0
H 0,25/12 LB
H 0,25/12 LB

Approvals

Standards and regulations

DIN 46228-4:1990	✓
------------------	---
