

2776.0
HZL/1,0-D RD
HZL/1,0-D RD



Wire-end ferrules, Max. wire cross-section: 1 mm², Length: 15 mm, Length of copper pipe: 8 mm, Colour: Red

Business data

Product description	Ferrules
Packaging unit	500
Quantity unit	PC
Weight per piece (not including packaging)	0.15
Weight per piece (including packaging)	0.16
Unit of weight	G
Customs number	85369010
Country of origin	DE

2776.0

HZL/1,0-D RD

HZL/1,0-D RD

Technical Data

Dimensions

Length	15 mm
Length of copper pipe	8 mm
Width of plastic collar	3.2 mm
Height of plastic collar	5.8 mm
Diameter of copper pipe	2 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.3 mm

Connection data

Wire cross-section, max.	1 mm ²
Wire cross-section AWG, max.	17
Stripping length	12 mm
2-wire plastic collar	✓

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer

2776.0
HZL/1,0-D RD
HZL/1,0-D RD

Technical Data

Materials

Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

2776.0
HZL/1,0-D RD
HZL/1,0-D RD

Approvals

Standards and regulations

DIN 46228-4:1990	✓
------------------	---
