

28165.7
PVC-TAA 7X20 K WH
PVC-TAA 7X20 K WH



Device and installation marker, Length: 20 mm, Width: 7 mm, Colour: White

Business data

Product description	Device and installation marker
For manufacturer type	Siemens Sirius
Packaging unit	600
Quantity unit	PC
Number of markers per card	60
Weight per piece (not including packaging)	0.3
Weight per piece (including packaging)	0.3
Unit of weight	G
Customs number	39199080
Country of origin	IT

28165.7

PVC-TAA 7X20 K WH

PVC-TAA 7X20 K WH

Technical Data

Dimensions

Length	20 mm
Width	7 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	179

28165.7

PVC-TAA 7X20 K WH

PVC-TAA 7X20 K WH

Accessories

Printer



Thermal transfer printer

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28000.0	TTPCard	4044211207397	1 PC

Inlays



Printer inlay

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28041.0	CCI-PC/PVC/PVCF	4044211208097	1 PC