ISSUE NUMBER THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED ORIGINAL (1)DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25 .XX ±0.13 .XXX ±0.10 30.80 ±0.38 10.7 24.99 ±0.25 42 -6.0 ±0.35 10.8 16.30 ±0.15 ۲ ***** ۲ 10° NOTES: MATERIAL: mmm HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 ⊣ SHELL: STEEL, Sn or Ni PLATED CONTACT: COPPER ALLOY SEE ORDERING GUIDE FOR PLATING 2.77 OPERATING TEMPERATURE: -55°C ~ 85°C CURRENT RATING: 3A PER CONTACT

CONTACT RESISTANCE: 25mQ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

628 SERIES D-SUB CONNECTOR		SW REFERENCE NO.: 628 ASSEMBLY		
		DRAWN: C.B	DATE: AUG. 01/2018	
		CHECKED:	DATE:	
EDAC INC TORONTO, ONTARIO CANADA R CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	1
		DRAWING NUMBER: 628-009	-321-056	ISSUE
		PART NUMBER: 628-009	-321-056	1



.<u>90 ±0.15</u> **12.6** ±0.38

~

2.84

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



YOUR