









ISOMETRIC



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 50VDC, 50mA
- ▲5. OPERATING FORCE: 260 ± 50gf
6. TRAVEL: 0.25mm ± 0.1mm
7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
- ▲9. SILVER CONTACTS
- ▲10. PACKAGING: TAPE AND REEL, 400 PCS PER REEL
11. ▲DENOTES CRITICAL PARAMETER
12. 2002/95/EC (ROHS) COMPLIANT

D	16571	UPDATE NOTES	10/24/2006	AR
C	15992	UPDATE NOTES	4/27/06	AR
B	14466	CORRECT NOTE 9	11/8/04	AR
A	13509	RELEASED FOR PRODUCTION	10/6/03	AR
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE TL3301CF260QG

SCALE 4:1

DATE 10/6/2003

DR AR

DWG D310539

REV D