

## EFD Cores (8995101021)



Part Number: 8995101021

98 EFD CORE SET

EFD (Economical Flat Design) cores have been designed to maximize volume in a low profile geometry. EFD cores allow maximum throughput power density with reasonably low mass for board level installation.

EFD cores can be supplied with the center post gapped to a mechanical dimension or an A<sub>t</sub> value.

## Catalog Drawing 3D Model

Weight indicated is per pair or set.

Weight: 0.9 (g)

| <u> </u> | 1t. 0.5 ( | <i>5)</i> |              |            |         |
|----------|-----------|-----------|--------------|------------|---------|
| Dim      | mm        | mm tol    | nominal inch | inch misc. |         |
| A        | 10.5      | ± 0.30    | 0.413        |            | ←B →    |
| В        | 5.2       | ± 0.15    | 0.205        |            |         |
| С        | 2.7       | ± 0.20    | 0.106        |            |         |
| D        | 3.75      | ± 0.15    | 0.148        |            | A L FE  |
| Е        | 7.65      | ± 0.30    | 0.301        |            |         |
| F        | 4.55      | ± 0.20    | 0.179        |            | , D, K, |
| K        | 1.45      | ± 0.10    | 0.057        |            |         |

## **Chart Legend**

 $\Sigma I/A$ : Core Constant,  $I_e$ : Effective Path Length,  $A_e$ : Effective Cross-Sectional Area,  $V_e$ :

Effective Core Volume
A<sub>1</sub>: Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

| Electrical Properties |          |  |
|-----------------------|----------|--|
| $A_L(nH)$             | 610 ±25% |  |
| Ae(cm <sup>2</sup> )  | 0.072    |  |
| $\Sigma l/A(cm^{-1})$ | 32.7     |  |
| l <sub>e</sub> (cm)   | 2.36     |  |
| $V_e(cm^3)$           | 0.171    |  |
| $A_{min}(cm^2)$       | 0.066    |  |

 $A_L$  value is measured at 1 kHz,  $B \le 10$  gauss.