

1 2 3 4 5 6 7 8

A

X
Kontaktanordnung
contact arrangement

31 27 23 19 15 11 7 3
29 25 21 17 13 9 5 1

64 Signal Kontakte
64 signal contacts

☒ = Kontaktposition belegt
= position with contact

☐ = Kontaktposition nicht belegt
= position without contact

B

X
(Montageausschnitt)
(mounting cutout)

2x
0,1 M

5,1 ± 0,1
8,7 ± 0,1

85 ± 0,1
90

0,1 A

C

D

X
Z

11,6 - 0,25

E

31x 2,54 (=78,74)
2,54
Reihe
row

1
a b

Position
position

85 - 0,2
90 ± 0,1
95 - 0,25

2,9 - 0,5
8,1 - 0,2
6 - 0,1
5,2 ± 0,3
2,54

F

1 2 3 4 5 6 7 8

09 02 264 6823

2

Au über/over Ni

Bestell-Nr.
part-no.

Anforderungsstufe nach IEC
performance level acc. to IEC

Kontaktüberfläche
contact plating

Techn. Character.
IEC 60603-2

Nicht tolerierte Maße / Free size tolerances
IEC 60603-2

Maßstab / Scale
1:1
(2:1)

Bauform B Federleiste,
Lötöse 5,2 64 pol.
type B female connector,
solder lug 5,2 64 pol.

HARTING

TB 09 02 264 x823

Blatt / page

33148
Mod.

Dat.

Name

HARTING Electronics GmbH & Co. KG
D-32339 ESPELKAMP

Sub.

 All Dimensions in mm Original Size DIN A 3			Techn. Character. IEC 60603-2			Nicht tolerierte Maß/Free size tolerances IEC 60603-2			
				Dat.	Name	Maßstab/Scale 1:1 (2:1)	Bauform B Federleiste, Lötöse 5,2 64 pol. <i>type B female connector, solder lug 5,2 64 pol.</i>		
			Detail.	11.11.05	Hage.				
			Insp.	11.11.05	Ge.				
			Stand.						
33148			HARTING Electronics GmbH & Co. KG D-32339 ESPELKAMP				TB 09 02 264 x823		Blatt/ page /
Mod.	Dat.	Name					Sub.		