

Specification Sheet

Part Number: 126-00001



1-Pc Cable Tie/Arrowhead Mount w/Wings, 6"L, 50lb, 0.24 - 0.26" Hole Dia, PA66HS, Black, 500/bag

Article Number	126-00001
Type	T50SL5
Color	Black (BK)
Features & Benefits	• Two piece assembly allows the mount to slide along the strap ensuring proper orientation. • Arrowhead style mount provides low insertion and high extraction force. • Arrowhead disc protects against dirt and other impurities.
Quantity Per	pcs.

Product Description	Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.	
Short Description	1-Pc Cable Tie/Arrowhead Mount w/Wings, 6"L, 50lb, 0.24 - 0.26" Hole Dia, PA66HS, Black, 500/bag	
Global Part Name	T50SL5-PA66HS-BK	
Minimum Tensile Strength (Imperial)	50.0	
Minimum Tensile Strength (Metric)	225	
Length L (Imperial)	6.5	
Length L (Metric)	165	
Fixation Method	Arrowhead	
Identification Plate Position	none	
Releasable Closure	No	
Tie Closure	plastic pawl	
Variant	Inside Serrated	
Width W (Imperial)	0.19	
Width W (Metric)	4.7	

Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.3
Bundle Diameter Max (Metric)	34.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.098
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.1 - 6.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.255
Mounting Hole Diameter D Max (Metric)	6.5

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	1.6