

Specification Sheet

Part Number: 126-00049



1-Pc Cable Tie/Arrowhead Mount w/Wings, 6"L, 50lb, 0.24 - 0.26" Hole Dia, PA66HIRHSUV, Black, 500/bag

Article Number	126-00049
Type	T50SSFM
Color	Black (BK)
Features & Benefits	• Two piece assembly allows the mount to slide along the strap ensuring proper orientation. • Arrowhead style mount provides low insertion and high extraction force. • Arrowhead disc protects against dirt and other impurities.
Quantity Per	bag

Product Description	Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.		
Short Description	1-Pc Cable Tie/Arrowhead Mount w/Wings, 6"L, 50lb, 0.24 - 0.26" Hole Dia, PA66HIRHSUV, Black, 500/bag		
Global Part Name	T50SSFMT-PA66HIRHSUV-BK		
Minimum Tensile Strength (Imperial)	50.0		
Minimum Tensile Strength (Metric)	225.0		
Length L (Imperial)	6.3		
Length L (Metric)	160.0		
Fixation Method	Arrowhead		
Identification Plate Position	none		
Releasable Closure	No		
Tie Closure	plastic pawl		
Variant	Inside Serrated		
Width W (Imperial)	0.18		
Width W (Metric)	4.6		

Bundle Diameter Min (Imperial)	0.13
Bundle Diameter Min (Metric)	3.2
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Height H (Imperial)	.20
Height H (Metric)	5.60
Panel Thickness Min(Imperial)	0.028
Panel Thickness Max(Imperial)	0.12
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.0 - 6.6 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.25
Mounting Hole Diameter D Max (Metric)	6.6

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.