

Specification Sheet

Part Number: 132-00009



Article Number	132-00009
Type	BT130LDP
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Unique two piece tie allows parallel entry and exit through the head for easy assembly.• High impact, heat stabilized material gives strength needed for trucking and heavy equipment applications.
Quantity Per	bag
Product Description	<p>The button head tie is a two piece tie providing for parallel entry and exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise prior to insertion into the head, enabling bi-directional looping.</p>

Short Description	Button Head Cable Tie with Retainers and Pilot Bushings, 15.0" Long, PA66HIRHSUV, Black, 50/pkg
Global Part Name	BT130LDP-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	130.0
Minimum Tensile Strength (Metric)	578.0
Length L (Imperial)	15.0
Length L (Metric)	381.5
Fixation Method	Connector Clip
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.3
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.25
Bundle Diameter Min (Metric)	6.4

Bundle Diameter Max (Imperial)	4.33
Bundle Diameter Max (Metric)	110.0
Mounting Hole Diameter D (Metric)	25.4 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Head	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)