

151-00756



Article Number: 151-00756

High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg



Download spec sheet

Base Data

Local Order Number	151-00756
Type	HDM375BDM4W
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Arched "H" profile surface allows for broad surface contact with the bundle, minimizing pinching and crushing of the bundles. • High Torque metal bushing allows for strength in heavy duty applications. • These mounts contain a small tab inside the mounting hole to temporarily engage the threads which allows assemblers to pre-install the mount on a stud with a washer and nut.
Product Description	High Torque Double Mounts are designed for routing multiple bundles with HellermannTyton heavy duty T250, T255, and wide strap cable ties to harness wires and hoses; however, they accept all standard cable ties up to .5" wide.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	High Torque Double Mnt, 4-Way, Mounting Hole .375", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Width W (Imperial)	1.4 "
Width W (Metric)	34.5 mm
Cable Tie Width Max. (Imperial)	0.5 "
Cable Tie Width Max. (Metric)	12.7 mm
Height H (Imperial)	1.0 "
Height H (Metric)	25.2 mm
Mounting Hole Diameter D (Imperial)	0.4 "
Mounting Hole Diameter D (Metric)	9.5 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100 Pieces

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1)	Yes

