

Specification Sheet

Part Number: 151-01454



Ratchet P-Clamp, 0.52" - 0.77" Bundle Dia, 30° Long, .33" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 200/ctn

Article Number	151-01454
Type	RCB30LM8
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• One-piece ratchet closure allows for easy installation during pre- or final assembly.• Easy release feature simplifies quick adjustments and maintenance.• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.• Zinc-plated steel mounting plate tolerates high torque and is treated to resist chemicals and salt spray.• Angled mounting plates are ideal for stacking RPCs or for avoiding obstructions or heat sources.
Quantity Per	carton

Product Description	<p>The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws.</p>		
Short Description	<p>Ratchet P-Clamp, 0.52" - 0.77" Bundle Dia, 30° Long, .33" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 200/ctn</p>		
Global Part Name	RCB30LM8-PA66HIRHSUV/ST/ZN-BK		
Minimum Tensile Strength (Imperial)	100.0		
Minimum Tensile Strength (Metric)	445.0		
Length L (Imperial)	5.93		
Length L (Metric)	150.5		
Fixation Method	Screw Mounting		
Variant	Long		
Width W (Imperial)	1.37		
Width W (Metric)	34.9		
Bundle Diameter Min (Imperial)	0.5		
Bundle Diameter Min (Metric)	12.7		

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.5
Cable Tie Width Max (Imperial)	0.52
Cable Tie Width Max (Metric)	13.2
Mounting Hole Diameter D (Imperial)	0.327
Mounting Hole Diameter D (Metric)	8.31 mm
Mounting Hole Diameter D Max (Metric)	8.31
Stud Diameter (Metric)	M8
Mounting Hole Centers (Imperial)	2.89

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Zinc plated (ZN) Steel (ST)

Material Shortcut PA66HIRHSUV ST ZN

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33) Yes

ROHS Complaint	Yes
-----------------------	-----

UL Listed (US and Canada)	Yes
----------------------------------	-----

UL Listed (US	Yes
----------------------	-----

Package Quantity(Imperial)	200
-----------------------------------	-----

Package Quantity (Metric)	200
----------------------------------	-----

Customs Number	3926909988
-----------------------	------------

Content Unit(BMEcat)	pcs.
-----------------------------	------