

Specification Sheet

Part Number: 151-01516



Ratchet P-Clamp, 1.38" - 2.01" Bundle Dia, 30° Long, .41" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 140/ctn

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-01516                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Type                | RCD30LM10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Features & Benefits | <ul style="list-style-type: none"><li>• One-piece ratchet closure allows for easy installation during pre- or final assembly.</li><li>• Easy release feature simplifies quick adjustments and maintenance.</li><li>• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li><li>• Zinc-plated steel mounting plate tolerates high torque and is treated to resist chemicals and salt spray.</li><li>• Angled mounting plates are ideal for stacking RPCs or for avoiding obstructions or heat sources.</li></ul> |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>                 | The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. |
| <b>Short Description</b>                   | Ratchet P-Clamp, 1.38" - 2.01" Bundle Dia, 30° Long, .41" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 140/ctn                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Global Part Name</b>                    | RCD30LM10-PA66HIRHSUV/ST/ZN-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Minimum Tensile Strength (Imperial)</b> | 100.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Minimum Tensile Strength (Metric)</b>   | 445.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Length L (Imperial)</b>                 | 8.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Length L (Metric)</b>                   | 215.9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Fixation Method</b>                     | Screw Mounting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Variant</b>                             | Long                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Width W (Imperial)</b>                  | 1.37                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Width W (Metric)</b>                    | 34.9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Bundle Diameter Min (Imperial)</b>      | 1.42                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Bundle Diameter Min (Metric)</b>        | 36.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                                              |                                                                                                      |
|----------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Bundle Diameter Max (Imperial)</b>        | 2.0                                                                                                  |
| <b>Bundle Diameter Max (Metric)</b>          | 51.0                                                                                                 |
| <b>Cable Tie Width Max (Imperial)</b>        | 0.52                                                                                                 |
| <b>Cable Tie Width Max (Metric)</b>          | 13.2                                                                                                 |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.405                                                                                                |
| <b>Mounting Hole Diameter D (Metric)</b>     | 10.29 mm                                                                                             |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 10.29                                                                                                |
| <b>Stud Diameter (Metric)</b>                | M10                                                                                                  |
| <b>Mounting Hole Centers (Imperial)</b>      | 3.17                                                                                                 |
| <b>Material</b>                              | Zinc plated (ZN) Steel (ST) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| <b>Material Shortcut</b>                     | PA66HIRHSUV ST ZN                                                                                    |
| <b>Flammability</b>                          | UL 94 HB                                                                                             |
| <b>UV Resistant (Yes/No)</b>                 | Yes                                                                                                  |
| <b>Operating Temperature (Metric)</b>        | -40°F to +221°F (-40°C to +105°C)                                                                    |
| <b>Reach Complaint(Article 33)</b>           | Yes                                                                                                  |

|                       |     |
|-----------------------|-----|
| <b>ROHS Complaint</b> | Yes |
|-----------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>UL Listed (US and Canada)</b> | Yes |
|----------------------------------|-----|

|                      |     |
|----------------------|-----|
| <b>UL Listed (US</b> | Yes |
|----------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| <b>Package Quantity(Imperial)</b> | 140 |
|-----------------------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>Package Quantity (Metric)</b> | 140 |
|----------------------------------|-----|

|                       |            |
|-----------------------|------------|
| <b>Customs Number</b> | 3926909988 |
|-----------------------|------------|

|                             |      |
|-----------------------------|------|
| <b>Content Unit(BMEcat)</b> | pcs. |
|-----------------------------|------|