

## Specification Sheet

Part Number: 151-01975



Ratchet P-Clamp, 0.76 - 1.42" Bundle Dia, 180° Short, .26" Hole Dia, PA66HIRHSUV/SS304, Black, 160/ctn

<b>Article Number</b>	151-01975
-----------------------	-----------

<b>Type</b>	RCC180SM6SS
-------------	-------------

<b>Color</b>	Black (BK)
--------------	------------

<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• One-piece ratchet closure allows for easy installation during pre- or final assembly.</li><li>• Easy release feature simplifies quick adjustments and maintenance.</li><li>• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li><li>• Stainless-steel mounting plate tolerates high torque and provides superior corrosion resistance against chemicals, salt spray and contact with dissimilar metals.</li><li>• Straight, 180° mounting plate is ideal for applications requiring a flush mount set off from the mounting hole.</li></ul>
--------------------------------	---

<b>Quantity Per</b>	carton
---------------------	--------

<b>Product Description</b>	The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws.
<b>Short Description</b>	Ratchet P-Clamp, 0.76 - 1.42" Bundle Dia, 180° Short, .26" Hole Dia, PA66HIRHSUV/SS304, Black, 160/ctn
<b>Global Part Name</b>	RCC180SM6SS-PA66HIRHSUV/SS304-BK
<b>Minimum Tensile Strength (Imperial)</b>	100.0
<b>Minimum Tensile Strength (Metric)</b>	445.0
<b>Length L (Imperial)</b>	6.15
<b>Length L (Metric)</b>	156.1
<b>Fixation Method</b>	Screw Mounting
<b>Variant</b>	Short
<b>Width W (Imperial)</b>	1.37
<b>Width W (Metric)</b>	34.9
<b>Bundle Diameter Min (Imperial)</b>	0.76
<b>Bundle Diameter Min (Metric)</b>	19.4

<b>Bundle Diameter Max (Imperial)</b>	1.42
<b>Bundle Diameter Max (Metric)</b>	36.0
<b>Cable Tie Width Max (Imperial)</b>	0.52
<b>Cable Tie Width Max (Metric)</b>	13.2
<b>Mounting Hole Diameter D (Imperial)</b>	0.256
<b>Mounting Hole Diameter D (Metric)</b>	6.5 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	6.5
<b>Stud Diameter (Metric)</b>	M6
<b>Mounting Hole Centers (Imperial)</b>	2.45

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Stainless Steel (SS304)

**Material Shortcut** PA66HIRHSUV SS304

**Flammability** UL 94 HB

**UV Resistant (Yes/No)** Yes

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**ROHS Complaint** Yes

<b>UL Listed (US and Canada)</b>	Yes
----------------------------------	-----

<b>UL Listed (US</b>	Yes
----------------------	-----

<b>Package Quantity(Imperial)</b>	160
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	160
----------------------------------	-----

<b>Customs Number</b>	3926909988
-----------------------	------------

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)