

## Specification Sheet

Part Number: 151-02009



Ratchet P-Clamp, 1.38" - 2.01" Bundle Dia, 180° Short, .33" Hole Dia, PA66HIRHSUV/SS304, Black, 160/ctn

### Article Number

151-02009

### Type

RCD180SM8SS

### Color

Black (BK)

### Features & Benefits

- One-piece ratchet closure allows for easy installation during pre- or final assembly.
- Easy release feature simplifies quick adjustments and maintenance.
- Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.
- Stainless-steel mounting plate tolerates high torque and provides superior corrosion resistance against chemicals, salt spray and contact with dissimilar metals.
- Straight, 180° mounting plate is ideal for applications requiring a flush mount set off from the mounting hole.

### Quantity Per

carton

<b>Product Description</b>	The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws.
<b>Short Description</b>	Ratchet P-Clamp, 1.38" - 2.01" Bundle Dia, 180° Short, .33" Hole Dia, PA66HIRHSUV/SS304, Black,160/ctn
<b>Global Part Name</b>	RCD180SM8SS-PA66HIRHSUV/SS304-BK
<b>Minimum Tensile Strength (Imperial)</b>	100.0
<b>Minimum Tensile Strength (Metric)</b>	445.0
<b>Length L (Imperial)</b>	7.15
<b>Length L (Metric)</b>	181.5
<b>Fixation Method</b>	Screw Mounting
<b>Variant</b>	Short
<b>Width W (Imperial)</b>	1.37
<b>Width W (Metric)</b>	34.9
<b>Bundle Diameter Min (Imperial)</b>	1.42
<b>Bundle Diameter Min (Metric)</b>	36.0

<b>Bundle Diameter Max (Imperial)</b>	2.0
<b>Bundle Diameter Max (Metric)</b>	51.0
<b>Cable Tie Width Max (Imperial)</b>	0.52
<b>Cable Tie Width Max (Metric)</b>	13.2
<b>Mounting Hole Diameter D (Imperial)</b>	0.327
<b>Mounting Hole Diameter D (Metric)</b>	8.31 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	8.31
<b>Stud Diameter (Metric)</b>	M8
<b>Mounting Hole Centers (Imperial)</b>	2.76

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Stainless Steel (SS304)
-----------------	--

<b>Material Shortcut</b>	PA66HIRHSUV SS304
--------------------------	-------------------

<b>Flammability</b>	UL 94 HB
---------------------	----------

<b>UV Resistant (Yes/No)</b>	Yes
------------------------------	-----

<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
---------------------------------------	-----------------------------------

<b>ROHS Complaint</b>	Yes
-----------------------	-----

<b>UL Listed (US and Canada)</b>	Yes
----------------------------------	-----

<b>UL Listed (US</b>	Yes
----------------------	-----

<b>Package Quantity(Imperial)</b>	160
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	160
----------------------------------	-----

<b>Customs Number</b>	3926909988
-----------------------	------------