

Specification Sheet

Part Number: 155-05400



1-Pc Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

Article Number	155-05400
Type	T50SOSSB5HEC
Color	Black (BK)
Features & Benefits	• Oval mount design pushes on easy by hand without the need for tools. • Design provides low insertion and high extraction force.
Quantity Per	bag
Product Description	The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables
Short Description	1-Pc Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

Global Part Name	T50SOSSB5HEC-PA66HS-BK
-------------------------	------------------------

Minimum Tensile Strength (Imperial)	50.0
--	------

Minimum Tensile Strength (Metric)	170
--	-----

Length L (Imperial)	6.0
----------------------------	-----

Length L (Metric)	160
--------------------------	-----

Fixation Method	Weld Stud Fixing
------------------------	------------------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Outside Serrated
----------------	------------------

Width W (Imperial)	0.19
---------------------------	------

Width W (Metric)	4.6
-------------------------	-----

Bundle Diameter Min (Imperial)	0.04
---------------------------------------	------

Bundle Diameter Min (Metric)	1.0
-------------------------------------	-----

Bundle Diameter Max (Imperial)	1.4
---------------------------------------	-----

Bundle Diameter Max (Metric)	35.0
-------------------------------------	------

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.35
Stud Length Max (Imperial)	0.63
Stud Length Max (Metric)	16.0
Stud Length Min (Metric)	11.0
Stud Diameter (Metric)	5.0 mm
Stud Diamater (Imperial)	0.2
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500

Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	2.75