

Specification Sheet

Part Number: 156-00072



Heavy Duty Cable Tie/Fir Tree Mount, 9" x .5", .04"—.62" Panel Thickness, PA66HIRHSUV, Black,100/pkg

Article Number	156-00072
Type	WSSFT9B
Color	Black (BK)
Features & Benefits	• Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation. • Fir tree provides low insertion effort yet demonstrates high extraction resistance. • Disc feature prevents rattling in high-vibration applications and protects against debris ingress.
Quantity Per	bag

Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.		
Short Description	Heavy Duty Cable Tie/Fir Tree Mount, 9" x .5", .04"–.62" Panel Thickness, PA66HIRHSUV, Black,100/pkg		
Global Part Name	WSSFT9B-PA66HIRHSUV-BK		
Minimum Tensile Strength (Imperial)	120.0		
Minimum Tensile Strength (Metric)	535		
Length L (Imperial)	9.0		
Length L (Metric)	228.0		
Fixation Method	Fir Tree		
Identification Plate Position	none		
Tie Closure	plastic pawl		
Variant	Inside Serrated		
Width W (Imperial)	0.5		
Width W (Metric)	12.7		
Bundle Diameter Max (Imperial)	2.3		

Bundle Diameter Max (Metric)	57.0
Height H (Imperial)	1.10
Height H (Metric)	28.50
Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.622
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	15.8
Mounting Hole Diameter D (Imperial)	0.34 - 0.36
Mounting Hole Diameter D (Metric)	8.7 - 9.2 mm
Mounting Hole Diameter D Min (Imperial)	0.34
Mounting Hole Diameter D Max (Imperial)	0.36
Mounting Hole Diameter D Max (Metric)	9.25
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.9

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
-----------------	--

Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.