

Specification Sheet

Part Number: 156-00282



Heavy Duty Cable Tie/Fir Tree Mount, 15" x .5"L, .03"—.28" Panel Thick, 50lb, PA66HS/PA66HIRHS, Black, 500/pkg

Article Number	156-00282
Type	T50LFT7
Color	Black (BK)
Features & Benefits	• Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation. • Fir tree provides low insertion effort yet demonstrates high extraction resistance. • Disc feature prevents rattling in high-vibration applications and protects against debris ingress.
Quantity Per	bag

Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
Short Description	Heavy Duty Cable Tie/Fir Tree Mount, 15" x .5"L, .03"-.28" Panel Thick, 50lb, PA66HS/PA66HIRHS, Black, 500/pkg
Global Part Name	T50LFT7-PA66HS/PA66HIRHS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	15.0
Length L (Metric)	380.0
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.16

Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	3.4
Bundle Diameter Max (Metric)	85.0
Height H (Imperial)	.78
Height H (Metric)	19.80
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.276
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.8
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.9

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
-----------------	--

Material Shortcut	PA66HIRHS PA66HS
--------------------------	------------------

Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
---------------------------	--

Flammability	UL 94 HB
---------------------	----------

Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
---------------------------------------	-----------------------------------

ROHS Complaint	Yes
-----------------------	-----

Package Quantity(Imperial)	500
-----------------------------------	-----

Package Quantity (Metric)	500
----------------------------------	-----

Customs Number	3926909988
-----------------------	------------