

Specification Sheet

Part Number: 156-00444



1-Pc Cable Tie/Arrowhead Mount with Seal, 8.5" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag

Article Number	156-00444
Type	T50ROSAH6MDU
Color	Natural (NA)
Features & Benefits	• An all-in-one bundling and fastening solution that saves time and reduces costs. • Foam seal prevents ingress of moisture and debris and prevents vibration.
Quantity Per	bag
Product Description	The arrowhead design of these ties offers a low insertion force and a high extraction force. The foam rubber seal provides additional protection against moisture and debris. One-piece mounting ties offer a complete solution by simultaneously bundling and mounting cables, wires and hoses.

Short Description	1-Pc Cable Tie/Arrowhead Mount with Seal, 8.5" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag
Global Part Name	T50ROSAH6MDU-PA66HIRHS-NA
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.5
Length L (Metric)	216.0
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.2
Width W (Metric)	5.0
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6

Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.0
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.08
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.1
Mounting Hole Diameter D (Imperial)	0.248 - 0.252
Mounting Hole Diameter D (Metric)	6.2 - 6.6 mm
Mounting Hole Diameter D Min (Imperial)	0.248
Mounting Hole Diameter D Max (Imperial)	0.252
Mounting Hole Diameter D Max (Metric)	6.6
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS

Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988