

Specification Sheet

Part Number: 156-01796



Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag

Article Number	156-01796
Type	T50ROSBHMB
Color	Black (BK)
Features & Benefits	• Delivers high extraction force for reliable performance, yet it's easy to install. • Reusable fastener can be removed from threaded or nonthreaded holes using a 5/16" hex driver. • Heat stabilized material provides excellent resistance to high temperatures.
Quantity Per	bag

Product Description	HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The 2-piece design includes a heat stabilized cable tie and formula-matched, 1/4" mount that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver. This ensures fastener can be reused.		
Short Description	Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag		
Global Part Name	T50ROSBHMB-PA66HS-BK		
Minimum Tensile Strength (Imperial)	50.0		
Minimum Tensile Strength (Metric)	225.0		
Length L (Imperial)	8.0		
Length L (Metric)	203.2		
Identification Plate Position	none		
Width W (Imperial)	0.31		
Width W (Metric)	7.8		
Bundle Diameter Min (Imperial)	0.10		
Bundle Diameter Min (Metric)	2.5		
Bundle Diameter Max (Imperial)	1.97		

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.736
Height H (Metric)	18.7
Diameter D (imperial)	0.25
Diameter D (metric)	6.35
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.35 mm
Mounting Hole Diameter D Min (Imperial)	0.246
Mounting Hole Diameter D Max (Imperial)	0.254
Mounting Hole Diameter D Max (Metric)	6.45
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.