

Specification Sheet

Part Number: 157-00140



1-Pc Cable Tie/Fir Tree Mount with Disc, 6.7"L, .24"-.27" Mounting Hole, PA66HIRHSUV, Black, 500/pkg

Article Number	157-00140
Type	T50SOSFT6LG-E2
Color	Black (BK)
Features & Benefits	• Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas. • Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install. • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
Quantity Per	bag

Product Description	HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
Short Description	1-Pc Cable Tie/Fir Tree Mount with Disc, 6.7"L, .24"—.27" Mounting Hole, PA66HIRHSUV, Black, 500/pkg
Global Part Name	T50SOSFT6LG-E2-PA66HIRHSUV-BK
Technical Description	Quote and Sell to Sumitomo Only. Please order 157-00296 for future sales.
Minimum Tensile Strength (Imperial)	40.5
Minimum Tensile Strength (Metric)	180.0
Length L (Imperial)	6.7
Length L (Metric)	167.0
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18

Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.04
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	.60
Height H (Metric)	16.10
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.3
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.25
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27

Mounting Hole Diameter D Max (Metric)	6.9
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)