HellermannTyton

Specification Sheet

Part Number: 166-90788



HelaGuard NM Ultra IP68 Fitting, 90-Degree Elbow, 0.75" NPT Thread, .75" Dia., PA66, Black, 1/pkg

Article Number	166-90788
Туре	HGU075-90-0750
Color	Black (BK)
Features & Benefits	 Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability. True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits. All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force. Elbow features a smooth bore to ease cable installation. PA66 nylon material has high resistance to salts, oils, weak acids, and solvents. Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

Quantity Per

Product Description	Elbow Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.
Short Description	HelaGuard NM Ultra IP68 Fitting, 90-Degree Elbow, 0.75" NPT Thread, .75" Dia., PA66, Black, 1/pkg
Global Part Name	HGU075-90-0750-PA66-BK
Length L (Imperial)	2.60
Length L (Metric)	66.0
Variant	90° Elbow
Outside Diameter OD(Imperial)	1.73
Outside Diameter OD(metric)	44.0
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	28

Material

Polyamide 6.6 (PA66)

Material Shortcut

Flammability	Self-Extinguishing
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Listed (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions