

Specification Sheet

Part Number: 170-03057



Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 100 ft/bulk reel

Article Number	170-03057
-----------------------	-----------

Type	BSHTTST134SRB
-------------	---------------

Color	Silver (SR)
--------------	-------------

Features & Benefits	• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application.
--------------------------------	--

Quantity Per	reel
---------------------	------

Product Description	High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.
----------------------------	--

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 100 ft/bulk reel
Global Part Name	BSHTTST134SRB-AL/GF-SR
Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.687
Bundle Diameter Max (Metric)	42.8
Diameter D (imperial)	1.75
Diameter D (metric)	44.4
Nominal Diameter (Imperial)	1.75
Nominal Diameter (Metric)	44.5
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64

Material	Glass Fiber (GF) Aluminum (AL)
Material Shortcut	AL GF
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	7019905050
Weight (Metric)	3.36
Weight (Imperial)	7.40