

Specification Sheet

Part Number: 170-03122



Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 1.5" Dia, PET, Black, 250 ft/bulk reel

Article Number	170-03122
Type	BSSCFR1120B
Color	Black (BK)
Features & Benefits	• Provides fuller coverage and a medium-to-high abrasion resistance. • Expands for ease of installation in either the shop or the field. • Increased braid density coverage provides higher level of abrasion resistance without losing flexibility. • Contains white tracer thread for simple identification of flame retardancy. • Treated yarns extinguish quickly and reduces potential flame spread to surrounding components. • Cuts with ordinary scissors without fraying ends.
Quantity Per	reel

Product Description	This protective sleeving is self-extinguishing and can be cut with sharp scissors instead of a hot knife for fray-resistant ends. Readily used in the automotive, audiovisual, industrial, wire, cable and computer industries where flame retardancy is required to reduce the likelihood of ignition and/or reduce the rate of flame spread. It is suited for situations where access to a hot knife is either impractical or impossible.
Short Description	Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 1.5" Dia, PET, Black, 250 ft/bulk reel
Global Part Name	BSSCFR1120B-PET-BK
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	1.25
Bundle Diameter Min (Metric)	31.8
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.8
Diameter D (imperial)	2.0
Diameter D (metric)	50.8
Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	38.1

Material	Polyester (PET)
Material Shortcut	PET
Flammability	Mil-202 UL VW-1 Limited Fire Hazard Halogen-Free Low Smoke Generation Low generation of toxic gases and corrosive acid
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	5808100000
Weight (Metric)	2.1
Weight (Imperial)	4.63

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)