

Specification Sheet

Part Number: 173-61400



Electromagnetic Protection Braided Sleeving, Flame Retardant, 14 mm Dia,PET;TNCU, TCBK, 328ft/Reel

Article Number	173-61400
-----------------------	-----------

Type	HEGEMIPV014
-------------	-------------

Color	Tin-coloured and Black (TCBK)
--------------	-------------------------------

Features & Benefits	• The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling. • The special combination of tin-plated copper and PBTVO yarn offers optimal inside and outside abrasion resistance. • In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.
--------------------------------	---

Quantity Per	metre
---------------------	-------

Product Description	HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.
Short Description	Electromagnetic Protection Braided Sleeving, Flame Retardant, 14 mm Dia,PET;TNCU, TCBK, 328ft/Reel
Global Part Name	HEGEMIPV014-PBT/SNCU-SR
Length L (Imperial)	328.0
Length L (Metric)	100.0
Bundle Diameter Min (Imperial)	0.47
Bundle Diameter Min (Metric)	12
Bundle Diameter Max (Imperial)	0.71
Bundle Diameter Max (Metric)	18
Diameter D (imperial)	0.55
Diameter D (metric)	14
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	14

Material	Tin-plated copper (SNCU) Polyester (PBT)
Material Shortcut	SNCU PBT
Flammability	FMVSS 302 UL 94 V0
Halogen free	No
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	328
Package Quantity (Metric)	100
Customs Number	5808100000
Content Unit(BMEcat)	metre
Weight (Imperial)	11.53