

Specification Sheet

Part Number: 181-42012



Slotted Wall Wiring Duct, 4" x 2", Adhesive, PVC, Gray, 30ft/Box

Article Number	181-42012
Type	SLA4X2
Color	Gray (GY)
Features & Benefits	• Strong fingers prevent unintended breaking. • Fingers are easily deflected outward, allowing easier positioning of the wires. • Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection. • Nonpermanent adhesive allows repositioning prior to final installation. • Optional covers snap on and off easily, and their nonslip lining ensures they stay in place even under vibration.
Quantity Per	box

Product Description	HellermannTyton Slotted Wall Duct features breakaway fingers that provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and Ts. Pressure-sensitive, rubber-based adhesive backing aids in temporary positioning.
Short Description	Slotted Wall Wiring Duct, 4" x 2", Adhesive, PVC, Gray, 30ft/Box
Global Part Name	SLA4X2-PVC-GY
Technical Description	Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	4.0
Width W (Metric)	101.6
Height H (Imperial)	2.07
Height H (Metric)	52.6
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)

Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013
UL Recognized (US)	Yes
Package Quantity(Imperial)	30
Package Quantity (Metric)	9.14
Customs Number	3925900000