

## Specification Sheet

Part Number: 184-12000



High-Density Slotted-Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 30ft/box

**Article Number** 184-12000

**Type** SLHD1X2

**Color** Gray (GY)

**Features & Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

**Quantity Per** box

|   |   |
|---|---|
| <b>Product Description</b>              | Pro-Duct high density, slotted wall wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| <b>Short Description</b>                | High-Density Slotted-Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 30ft/box   |
| <b>Global Part Name</b>                 | SLHD1X2-PVC-GY  |
| <b>Technical Description</b>            | Non-Adhesive  |
| <b>Length L (Imperial)</b>              | 6.0   |
| <b>Length L (Metric)</b>                | 1.83  |
| <b>Width W (Imperial)</b>               | 1.0   |
| <b>Width W (Metric)</b>                 | 25.4  |
| <b>Height H (Imperial)</b>              | 2.07  |
| <b>Height H (Metric)</b>                | 52.6  |
| <b>Mounting Hole Centers (Imperial)</b> | 2.0   |
| <b>Material</b>                         | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>                | PVC   |

|  |  |
|--|--|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No   |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No   |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | EN 50085-1:2005 + A1:2013 CSA UL EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 30   |
| <b>Package Quantity (Metric)</b>       | 9.14   |
| <b>Customs Number</b>                  | 3925900000                                       |