


Specification Sheet

Part Number: 553-50035



ShrinkTrak Labels, 1-Sided, 1-Slit, .75" (19.05mm), PO-X, White, 500/box

Article Number	553-50035
Type	HST18-6WH-S
Color	White (WH)
Features & Benefits	• Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box

Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
Short Description	ShrinkTrak Labels, 1-Sided, 1-Slit, .75" (19.05mm), PO-X, White, 500/box
Global Part Name	HST18-6WH-S-PO-X-WH
Variant	Thin-Wall
Width W (Imperial)	0.95
Width W (Metric)	24.13
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	1.2
Height H (Metric)	30.48
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.75
Outside Diameter OD(metric)	19.05

Outside Diameter Max(Imperial)	0.75
Outside Diameter Max (metric)	19.05
Wall Thickness WT (Imperial)	0.036
Wall Thickness WT (Metric)	0.914
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
US MIL SPEC	MIL-STD-202G Method 215K SAE-AMS-DTL-23053/5 Class 1 and 3 SAE-AS81531
Flammability	UL 224 VW-1
Halogen free	No
Operating Temperature (Metric)	-67°F to +275°F (-55°C to +135°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 224 125 °C 600V VW-1
Package Quantity(Imperial)	500

Package Quantity (Metric)	500
Customs Number	3917320000
Content Unit(BMEcat)	pack
Labels per Column	1
Labels per Row	2
Weight (Metric)	0.68
Weight (Imperial)	1.48