

Specification Sheet

Part Number: 553-50042



ShrinkTrak Labels, 1-Sided, 1-Slit, 1.0" (25.4mm), PO-X, Yellow, 500/box

|                     |                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 553-50042                                                                                                                                                                                                                                                                                                                                                                 |
| Type                | HST24-8YE-S                                                                                                                                                                                                                                                                                                                                                               |
| Color               | Yellow (YE)                                                                                                                                                                                                                                                                                                                                                               |
| Features & Benefits | <ul style="list-style-type: none"><li>• Slide Slit and optional center slits for easy wire insertion.</li><li>• Smooth surface for clean and legible printing.</li><li>• Supplied on a ladder style carrier so that markers can be kitted after printing.</li><li>• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.</li></ul> |
| Quantity Per        | box                                                                                                                                                                                                                                                                                                                                                                       |

|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>           | HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production. |
| <b>Short Description</b>             | ShrinkTrak Labels, 1-Sided, 1-Slit, 1.0" (25.4mm), PO-X, Yellow, 500/box                                                                                                                                                                                                                                                                                                                                              |
| <b>Global Part Name</b>              | HST24-8YE-S-PO-X-YE                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Variant</b>                       | Thin-Wall                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Width W (Imperial)</b>            | 0.95                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Width W (Metric)</b>              | 24.13                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Thickness T (Imperial)</b>        | .003                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Thickness T (Metric)</b>          | .0762                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Height H (Imperial)</b>           | 1.69                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Height H (Metric)</b>             | 42.92                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Width of Liner (Metric)</b>       | 76.2                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Width of Liner (imperial)</b>     | 3.0                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Outside Diameter OD(Imperial)</b> | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Outside Diameter OD(metric)</b>   | 25.4                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                                        |                                                                              |
|----------------------------------------|------------------------------------------------------------------------------|
| <b>Outside Diameter Max(Imperial)</b>  | 1.0                                                                          |
| <b>Outside Diameter Max (metric)</b>   | 25.4                                                                         |
| <b>Wall Thickness WT (Imperial)</b>    | 0.039                                                                        |
| <b>Wall Thickness WT (Metric)</b>      | 0.99                                                                         |
| <b>Material</b>                        | Polyolefin, cross-linked (PO-X)                                              |
| <b>Material Shortcut</b>               | PO-X                                                                         |
| <b>US MIL SPEC</b>                     | SAE-AS81531<br>SAE-AMS-DTL-23053/5 Class 1 and 3<br>MIL-STD-202G Method 215K |
| <b>Flammability</b>                    | UL 224 VW-1                                                                  |
| <b>Halogen free</b>                    | No                                                                           |
| <b>Operating Temperature (Metric)</b>  | -67°F to +275°F (-55°C to +135°C)                                            |
| <b>Reach Complaint(Article 33)</b>     | Yes                                                                          |
| <b>ROHS Complaint</b>                  | Yes                                                                          |
| <b>Certification/Specification WEB</b> | UL 224 125 °C 600V VW-1                                                      |
| <b>Package Quantity(Imperial)</b>      | 500                                                                          |

|                                  |            |
|----------------------------------|------------|
| <b>Package Quantity (Metric)</b> | 500        |
| <b>Customs Number</b>            | 3917320000 |
| <b>Content Unit(BMEcat)</b>      | pack       |
| <b>Labels per Column</b>         | 1          |
| <b>Labels per Row</b>            | 2          |
| <b>Weight (Metric)</b>           | 0.68       |
| <b>Weight (Imperial)</b>         | 1.48       |