

## Specification Sheet

Part Number: 556-00239



TT230SM Printer Kit, 1/pkg

**Article Number**

556-00239

**Type**

TT230SM KIT

**Color**

Black (BK)

**Features & Benefits**

- 300 dpi print head for high resolution printing.
- Label holder included for easy loading of any size media.
- Lightweight with a small footprint for easy transport to jobs sites or around the shop.
- LCD user interface for easier setup, diagnostics and adjustments.
- Ethernet ready for easy network connectivity.
- Print speeds up to 3 in (76.2mm) per second for fast label production.
- 2mb flash/8mb DRAM for accepting large label files that require a lot of data.
- Highly accurate sensor means there is no need to calibrate during label changes and eliminates most common printer errors.

**Quantity Per**

EA

<b>Product Description</b>	HellermannTyton's TT230 Series thermal transfer printers are designed for low- to medium-volume printing of thermal transfer labels and ShrinkTrak. They deliver optimal performance not found in other small desktop printers. This lightweight printer offers high speed, precision and flexible printing with the ability to print on most HellermannTyton labels and ShrinkTrak. Used in conjunction with TagPrint Pro, the printers offer error-free printing and seamless operation. Each kit contains one TT230SM printer (556-00230), a carrying case (556-00231), a ribbon (TT822OUTSM), label holder (556-00235) and TagPrint Pro 4.0 software (556-00035).
<b>Short Description</b>	TT230SM Printer Kit, 1/pkg
<b>Global Part Name</b>	TT230SM KIT-PL-BK
<b>Technical Description</b>	Thermal Transfer Printer, Black
<b>Contents of pkg/kit</b>	One TT230SM printer, label caddy, TagPrint® Pro label design software, black ribbon, and a high-quality hard-shell case.
<b>Length L (Imperial)</b>	10.0
<b>Length L (Metric)</b>	254.0
<b>Width W (Imperial)</b>	7.95
<b>Width W (Metric)</b>	201.9
<b>Height H (Imperial)</b>	13.5
<b>Height H (Metric)</b>	342.9

<b>Material</b>	Plastic (PL)
<b>Material Shortcut</b>	PL
<b>Operating Temperature (Metric)</b>	+40°F to +104°F (+4°C to +40°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	1
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	8443321050
<b>Weight (Metric)</b>	2
<b>Weight (Imperial)</b>	4.41