


596-00831

Article Number: 596-00831

Pre-Printed Metal Solar Placard, "WARNING - DC CONDUCTORS MAY BE...", 3.75" X 2.0", Aluminum, Orange/Silver, 5/PK



Base Data

Local Order Number	596-00831
Type	WDCCUM5
Color	Orange (OG)
Features and Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance• Supplied with aggressive adhesive to ensure long life• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	3.75" X2" Black text on Orange/Silver Aluminum background that reads as: "WARNING - ELECTRICAL SHOCK HAZARD. THE DC CONDUCTORS OF THIS PHOTOVOLTAIC SYSTEM ARE UNGROUNDED AND MAY BE ENERGIZED" - 5 per pack.
Short Description	Pre-Printed Metal Solar Placard, "WARNING - DC CONDUCTORS MAY BE...", 3.75" X2.0", Aluminum, Orange/Silver, 5/PK

Product Dimensions

Length L (Imperial)	3.75 "
Length L (Metric)	95.25 mm
Width W (Imperial)	3.75 "
Width W (Metric)	95.25 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	1
Package Quantity (Metric)	5

Material and Specifications

Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	3M 300LSE Ultra High Bond Permanent Acrylic Adhesive
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	from +50°F (from +10°C)

Halogenfree	Yes
Operating Temperature	-40°F to +203°F (-40°C to +95°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes