



# Specification Sheet

Part Number: 596-00842

**PHOTOVOLTAIC**

**DC DISCONNECT**

Metal Solar Placard, Hand Writable, PV DC DISCONNECT, 3.75" x 1.0", AA, Black, 5/pkg

Article Number	596-00842
Type	DCDISCTM5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.</li><li>• Aggressive adhesive ensures strong bond, even on powder coated surfaces.</li><li>• Meets or exceeds NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability.</li><li>• Optional Paint Shields provide additional protection for pre-printed and variable data placards.</li></ul>
Quantity Per	pack

<b>Product Description</b>	Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.
<b>Short Description</b>	Metal Solar Placard, Hand Writable, PV DC DISCONNECT, 3.75" x 1.0", AA, Black, 5/pkg
<b>Global Part Name</b>	DCDISCTM5-AA-BK
<b>Technical Description</b>	3.75" X 1" Silver aluminum text on black background that reads as: "PHOTOVOLTAIC DC DISCONNECT." - 10 per pack. Nameplate is also printable using a paint pen to add variable voltage information on demand.
<b>Local Order Number 2</b>	Cross Reference = Paint Shield: 596-00796
<b>Length L (Imperial)</b>	3.75
<b>Length L (Metric)</b>	95.25
<b>Width W (Imperial)</b>	3.75
<b>Width W (Metric)</b>	95.25
<b>Height H (Imperial)</b>	1.00
<b>Height H (Metric)</b>	25.40

<b>Material</b>	Anodized Aluminum (AA)
<b>Material Shortcut</b>	AA
<b>Adhesive</b>	Ultra High Bond Permanent Acrylic Adhesive
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	from +50°F (from +10°C)
<b>Operating Temperature (Metric)</b>	-40°F to +203°F (-40°C to +95°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	NEC2017 NEC2014
<b>Warranty (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	5
<b>Package Quantity (Metric)</b>	5
<b>Customs Number</b>	7616995195
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	.104

**Weight (Imperial)** 0.23